



The Euclid Chemical Company

SUPER DIAMOND CLEAR VOX - 55 GAL

Version 1.1

Print Date 08/19/2006

REVISION DATE: 08/18/2006

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : SUPER DIAMOND CLEAR VOX - 55 GAL
 Product code : 359Z 55

COMPANY : Euclid Chemical Company
 19218 Redwood Road
 Cleveland, OH 44110

Telephone : 1-800-321-7628
 Emergency Phone: : U.S. only: 1-800-255-3924
 International Users Call Collect: 1-813-248-0585

Product use : Coating

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

White. Liquid solution. No serious effects anticipated under normal conditions of use. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : No serious effects anticipated under normal conditions of use.
 Eyes : Direct contact may cause mild irritation.
 Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.
 Skin : May cause mild irritation.

Aggravated Medical Conditions


Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Prolonged or repeated contact/exposure to aromatic petroleum distillates may cause defatting, drying, and irritation of the skin, dermatitis, and central nervous system (CNS) effects. This product contains naphthalene. A National Toxicology Program (NTP) draft report states that lifetime inhalation exposure to naphthalene resulted in increases in tumors of the nose in rats. In a previous NTP study, lifetime inhalation exposure to naphthalene increased lung tumors in female mice. The relevance of the rodent findings to humans is questionable. Styrene was reported to cause liver and kidney damage in experimental animals at high levels of exposure. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Water	7732-18-5	40.0 - 70.0
Styrene Ethylhexyl Acrylate Copolymer	NJ TSRN# 51721300-5841P	15.0 - 40.0
Aromatic petroleum distillates	64742-95-6	5.0 - 10.0
Heavy aromatic naphtha	64742-94-5	5.0 - 10.0



SUPER DIAMOND CLEAR VOX - 55 GAL

Version 1.1

Print Date 08/19/2006

REVISION DATE: 08/18/2006

Isobutyric acid polymer	25265-77-4	3.0 - 7.0
1,2,4-Trimethylbenzene	95-63-6	1.0 - 5.0
Naphthalene	91-20-3	<1.0
Styrene	100-42-5	<1.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for 15 minutes. If irritation persists, get medical attention.
- Skin contact : Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Get medical attention. Do not induce vomiting.
- Notes to physician : Not applicable.

SECTION 5 - FIRE FIGHTING MEASURES

- Flash point : > 200 °C, > 392 °F
- Method : Setaflash Closed Cup
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : This product is not expected to burn under normal conditions of use.
- Hazardous combustion products : Carbon monoxide and carbon dioxide can form. Smoke, fumes.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
- Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Transfer to appropriate container for disposal. Stop flow. Contain spill. Keep out of water courses. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal. Use appropriate protective equipment. Avoid contact with material.

SECTION 7 - HANDLING AND STORAGE

Handle in compliance with common hygienic practices. Clean hands thoroughly after handling. Keep from freezing. Do not use in confined or poorly ventilated areas. Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Store in sealed containers in a dry, ventilated warehouse location above freezing.



SUPER DIAMOND CLEAR VOX - 55 GAL

Version 1.1
 REVISION DATE: 08/18/2006

Print Date 08/19/2006

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment


- Respiratory protection : Not required under normal conditions of use. Wear appropriate, NIOSH/MSHA approved respirator with combination particulate filter and vapor/gas removing cartridge when the ventilation is not adequate or if it is necessary to abrade or grind surfaces coated with this product.
- Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection : Prevent contact with shoes and clothing. Use rubber apron and overshoes.
- Protective measures : Other equipment not normally required. Use professional judgment in the selection, care, and use.
- Engineering measures : Not required under normal conditions of use. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
1,2,4-Trimethylbenzene	95-63-6	ACGIH TWA:	25 ppm	
Naphthalene	91-20-3	ACGIH TWA: ACGIH STEL: OSHA PEL:	10 ppm 15 ppm 50 mg/m3	
Styrene	100-42-5	ACGIH TWA: ACGIH STEL: OSHA TWA:	20 ppm 40 ppm 100 ppm	

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Form : Liquid solution
- Color : White
- Odor : AromaticHydrocarbon
- pH : 9.7 - 10.1
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : 212 °F, 100 °C



SUPER DIAMOND CLEAR VOX - 55 GAL

Version 1.1

Print Date 08/19/2006

REVISION DATE: 08/18/2006

Water solubility : Soluble
 Specific Gravity : 1
 % Volatile Weight : 70.5 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid : Strong acids.Strong bases.
 Stability : Stable
 Hazardous polymerization : Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Naphthalene, CAS-No.: 91-20-3
 Acute oral toxicity (LD-50 oral) 2,600 mg/kg (Sprague-Dawley rat)
 Acute dermal toxicity (LD-50 dermal) 20,000 mg/kg (Rat)
 Styrene, CAS-No.: 100-42-5
 Acute oral toxicity (LD-50 oral) 1,000 mg/kg (Rat)
 Acute inhalation toxicity (LC-50) 2,770 mg/l (Rat)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Incinerate at EPA approved facility or dispose of waste in compliance with state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

TDG / DOT Shipping Description:
 NOT REGULATED

SECTION 15 - REGULATORY INFORMATION

North American Inventories:
 All components are listed or exempt from the TSCA inventory.
 This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:
 SARA 313 Components : 1,2,4-Trimethylbenzene 95-63-6
 Naphthalene 91-20-3



SUPER DIAMOND CLEAR VOX - 55 GAL

Version 1.1

Print Date 08/19/2006

REVISION DATE: 08/18/2006

Styrene 100-42-5

SARA 311/312 Hazards : Acute Health Hazard

OSHA Hazardous Components :

1,2,4-Trimethylbenzene 95-63-6
 Naphthalene 91-20-3
 Styrene 100-42-5

OSHA Status: Considered : Irritant
 hazardous based on the
 following criteria:

OSHA Flammability : IIIB

Regulatory VOC (less water and : 347 g/l
 exempt solvent)
 VOC Method 310 : 9 %

U.S. State Regulations:

MASS RTK Components : 1,2,4-Trimethylbenzene 95-63-6

Penn RTK Components : Water 7732-18-5
 Styrene Ethylhexyl Acrylate
 Copolymer NJ TSRN# 51721300-5841P
 Aromatic petroleum distillates 64742-95-6
 Heavy aromatic naphtha 64742-94-5
 Isobutyric acid polymer 25265-77-4
 1,2,4-Trimethylbenzene 95-63-6

NJ RTK Components : Water 7732-18-5
 Styrene Ethylhexyl Acrylate
 Copolymer NJ TSRN# 51721300-5841P
 Aromatic petroleum distillates 64742-95-6
 Heavy aromatic naphtha 64742-94-5
 Isobutyric acid polymer 25265-77-4
 1,2,4-Trimethylbenzene 95-63-6

Chemicals known to the State of California to cause cancer birth defects and/or other reproductive harm:
 91-20-3 Naphthalene

SECTION 16 - OTHER INFORMATION

HMS Rating :

Health	2
Flammability	1
Reactivity	1
PPE	

0 = Minimum
 1 = Slight
 2 = Moderate
 3 = Serious
 4 = Severe



SUPER DIAMOND CLEAR VOX - 55 GAL

Version 1.1

REVISION DATE: 08/18/2006

Print Date 08/19/2006

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information System